

## H57M-ED65

### Specifications

#### CPU

- Supports Intel® i3 / i5 / i7 based processors in LGA1156 package.

Please refer to CPU Support for compatible CPU; the above description is for reference only.

#### Chipset

- Intel® H57 Chipset
- Supports QPI up to 6.4GT/s
- Hi-Speed USB (USB2.0) controller, 480Mb/sec.
- 6 SATAII ports with transfer rate up to 3Gb/s.
- PCI Master v2.3, I/O APIC.
- ACPI 2.0 compliant.

#### Main Memory

- Supports four unbuffered DIMM of 1.5 Volt DDR3 1066/1333/1600\*/2000\*/2133\* (OC) SDRAM, 16GB Max
- Supports 1Gb/ 2Gb/ 4Gb DRAM size
- Supports Dual channel mode

#### Slots

- 2 PCI Express gen2 x16 slot
- 2 PCI Express gen2 x1 slots

#### On-Board IDE/SATA

- One Ultra DMA 66/100/133 IDE controller integrated in JMicron® 363.
- Supports PIO, Bus Master operation modes.
- Can connect up to two Ultra ATA drives.
- SATAII controller integrated in Intel H55 chipset & JMicron® 363.
- Up to 3Gb/s transfer speed.
- Supports six SATAII ports by H55
- Supports one SATAII port by JMicron® 363
- Supports AHCI controller with AHCI / SATA RAID 0/1/5/10 by H57.

## Audio

- Chipset integrated by Realtek® ALC889
- Flexible 8-channel audio with jack sensing
- Compliant with Azalia 1.0 Spec
- Meet Microsoft Vista Premium spec

## LAN

- Supports one PCI Express LAN 10/100/1000 Fast Ethernet by Realtek 8111DL.

## Internal I/O Connectors

- ATX 24-Pin power connector
- 4-pin ATX 12V power connector
- CPU x 1 / System x 2 FAN connectors
- CD-in connector
- Front panel audio connector
- Front panel connector
- 1 x chasis intrusion connector
- 4 x USB 2.0 connectors
- 7 x Serial ATAII connectors
- 1 x ATA133 connector
- 1 x OC Switch
- 1 x Clear CMOS button
- 1 x Power button
- 1 x OC Genie button
- 1 x D-LED3 panel connector
- 2 Base clock control buttons
- 1 x SPDIF-out connector
- 1 x TPM module connector
- 1 x Serial port connectors
- 1 x Parallel port connector
- 1 x IEEE1394 connector

#### Back Panel I/O Ports

- 1 x PS/2 Keyboard
- 1 x PS/2 Mouse
- 4 x USB 2.0 ports
- 1 x RJ45 LAN Jack
- 1 x 6 in 1 audio jack
- 1 x HDMI port
- 1 x Graphic Card port
- 1 x DVI port
- 1 x Display Port
- 1 x IEEE1394 port
- 1 Optical S/PDIF-out port
- 1 x eSATA port

#### BIOS

- The mainboard BIOS provides "Plug & Play" BIOS which detects the peripheral devices and expansion cards of the board automatically.
- The mainboard provides a Desktop Management Interface(DMI) function which records your mainboard specifications.

#### Dimension

- 24.5cm(L) x 24.5cm(W) M-ATX Form Factor

#### Mounting

- 6 mounting holes.